



SYNTHETIC 5W-40 MOTOR OIL

Introduction

Petro-Canada Synthetic 5W-40 Passenger Car Motor Oil is formulated to meet demanding European and North American motor oil performance requirements for passenger cars, sport utility vehicles, vans and light trucks powered by gasoline or diesel engines. Synthetic 5W-40 meets or exceeds the requirements of ACEA A3/B4/C3, API SN/CF, MB 229.51, VW 502.00/505.00/505.01, BMW LL-04, Porsche and Ford M2C917-A. It also fulfills the engine oil requirements of those manufacturers who require ACEA credentials, such as Peugeot, Renault, Fiat and Rover.

Petro-Canada Synthetic 5W-40 is a fuel saving synthetic motor oil that is produced with high quality synthetic base oils and an advanced additive system.

Features and Benefits

- **Excellent Low Temperature Fluidity**
 - Provides fast cold weather engine starts
 - Provides vital engine wear protection during low temperature start-up
- **Excellent Resistance To High Temperature Lubricant Breakdown**
 - Extends engine life by minimizing sludge, varnish and carbon deposits on engine parts
- **Longer Oil Life and Lower Oil Consumption**
 - Formulated with a shear stable viscosity modifier for enhanced viscosity stability and better bearing protection.
- **Outstanding Wear Protection**
 - Formulated with premium anti-wear additives for enhanced wear protection

- Reduces wear on rings, liners and camshafts
- Extends bearing life
- **Surpasses Industry Performance Standards**
 - Exceeds the ACEA A3/B4/C3 for gasoline and light duty diesel engines
 - Meets the requirements of VW specification 502.00/505.00/505.01 Pump diesel and Mercedes Benz sheet 229.51

Applications

Petro-Canada Synthetic 5W-40 is recommended for use in gasoline and diesel powered engines in cars, SUVs, vans and light trucks.

It can be used as “top-up” to conventional motor oil of the same viscosity grade between oil changes, but best results will be achieved with a complete oil and filter change.

Petro-Canada Synthetic 5W-40 Passenger Car Motor Oil can provide additional protection and peace of mind under severe driving conditions such as:

- short trip
- stop-and-go with significant idling
- trailer towing
- extended high speed motorway driving
- extreme hot and cold temperatures

Even though Petro-Canada Synthetic 5W-40 is a high performance Synthetic Motor Oil, we recommend that you follow the Vehicle Manufacturer guidelines for oil and filter changes.

What is the HT difference?

Petro-Canada starts with the patented HT purity process to produce water-white, 99.9% pure base oils. The result is a range of lubricants, specialty fluids and greases that deliver maximum performance for our customers.



Typical Performance Data

PROPERTY	TEST METHOD	SYNTHETIC 5W-40
Colour	ASTM D1500	2.5
Flash Point, °C	ASTM D92	233
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	ASTM D445	82.8 14.0
Cold Cranking Viscosity, cP @ -30°C	ASTM D5293	5,045
Viscosity Index	ASTM D2270	172
Pour Point, °C	ASTM D5950	-45
Borderline Pumping Viscosity, cP @ -35°C	ASTM D4684	33,270
Sulphated Ash, %wt.	ASTM D874	0.8
Total Base Number (TBN), mg KOH /g	ASTM D2896	7.7

The values quoted above are typical of normal production. They do not constitute a specification.

Product Availability

Petro-Canada Synthetic 5W-40 Motor Oil is only available in Europe.

Health and Safety

To obtain Material Safety Data Sheet (MSDS), contact one of Petro-Canada's TechData Info Lines.

TechData Info Lines

If you would like to know more about **Petro-Canada's Synthetic 5W-40**, or any other product in our complete line of quality lubricants, please contact us at:

Lubricants Head Office
Petro-Canada Lubricants Inc.
2310 Lakeshore Road West
Mississauga, Ontario
Canada L5J 1K2



Canada - West Phone 1-800-661-1199
 - East (English) Phone 1-800-268-5850
 (French) Phone 1-800-576-1686
 Other Areas Phone (416) 730-2408
 E-mail lubecsr@suncor.com
 Website lubricants.petro-canada.ca

Petro-Canada Europe Lubricants Limited

Wellington House, Starley Way
Birmingham International Park
Solihull, B37 7HB, United Kingdom

Telephone +44 (0) 121 781 7264
 Fax +44 (0) 121 781 7401
 UK Website www.petro-canada.co.uk
 German Website www.petro-canada.de

Petro-Canada America Lubricants

980 North Michigan Avenue
Suite 1400, #1431
Chicago, Illinois
USA 60611

Phone 1-888-284-4572
 Fax 1-708-246-8994
 E-mail email@petro-canadaamerica.com

Petro-Canada Asia Pacific Holding Company Ltd.

Jia Shi Lubricants Trading (Shanghai) Co. Ltd.
1908 World Trade Tower
500 Guangdong Road, Huangpu District
Shanghai, China 200001

Phone +86-21-6362-0066
 Fax +86-21-6362-0536
 E-mail asiapacific@suncor.com
 Website www.petrocanada.cn