



Mobilube GX 80W-90, 140

Heavy Duty Automotive Gear Lubricants

Product Description

Mobilube GX 80W-90, 140 are high performance, heavy duty gear lubricants formulated from high quality base oils and an advanced additive system. These lubricants are engineered for automotive heavy-duty transmissions, axles, and final drives where protection against wear and scoring is required. They are recommended by ExxonMobil for use in applications where API GL-4 service is required.

Features and Benefits

Today's heavy equipment applications place higher performance demands on drivetrain lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube GX 80W-90, 140 is engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Good thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits Longer seal life
Excellent rust and corrosion protection	Longer component life
Good low temperature lubrication	Reduced wear at start-up and ease of start-up
Compatible with typical seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions, axles and final drives requiring API GL-4 level performance
- Passenger cars, on highway light and heavy duty trucks, and commercial vehicles
- Off highway industries including: construction, mining, quarrying, and agriculture
- Other heavy duty industrial and automotive applications including hypoid gears operating under moderate to severe conditions

Specifications and Approvals

Mobilube GX Gear Oils are recommended by ExxonMobil for use in applications requiring:	80W-90	140
API GL-4	X	X

Typical Properties

Mobilube GX Gear Oils Properties		
SAE Grade	80W-90	140
Viscosity, ASTM D 445		
cSt @ 40°C	135	447
cSt @ 100°C	14.5	30.0
Viscosity Index, ASTM D 2270	104	95
Pour Point, °C, ASTM D 97	-33	-6
Flash Point, °C, ASTM D 92	240	260
Density @ 15°C kg/l, ASTM D 4052	0.89	0.91

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube GX are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

1-2011

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that

include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2012 Exxon Mobil Corporation. All rights reserved.