

Product Information

MULTILIFE C-THREE 5W/40 FULLY SYNTHETIC ENGINE OIL

Description

Multilife C-THREE 5W/40 is a mid-SAPS (Sulphur, Ash, Phosphorus) synthetic multigrade engine oil specially formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils for gasoline and diesel engine applications.

Multilife C-THREE 5W/40 has been developed for use in Euro IV compliant vehicles using after treatment devices.

Multilife C-THREE 5W/40 provides:

1. Increased engine efficiency, output and fuel economy.
2. Excellent cold starting characteristics, reducing noise and wear.
3. Turbo-charger protection.
4. Improved flow rates to bearings at low temperatures and increased film strength at high temperatures.
5. Better high temperature operation and anti-sludge control.
6. Low levels of volatility.
7. Better thermal stability, improved engine cleanliness.
8. Mid-SAPS (Sulphur, Ash, Phosphorus) product, for improved DPF (Diesel Particulate Filter) performance.

Applications

Recommended for the latest petrol and passenger car diesel engines, including turbo and supercharged versions, requiring a lubricant of this performance and viscosity.

Performance Levels

API SM (SL)/CF

ACEA C3 - 08

BMW Longlife-04

Ford WSS-M2C917A

MB 229.31

Porsche

VW 502.00 / 505.00 / 505.01

Renault 0700 and 0710

Physical Characteristics

Density at 15°C	0.865	TBN, mg/KOH/g	7.4
Kinematic Viscosity at 100 °C, cSt.	14.85	Sulphated Ash, %Wt.	0.79
Kinematic Viscosity at 40 °C, cSt.	91	Pour Point, °C	-40
Viscosity Index	171		

(TDS Multilife C-THREE 5W/40 – 181110 Issue 2)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584