

Product Information

MULTIVIS SEMI-SYNTHETIC 10W/40

Description

Multivis 10W/40 is a semi-synthetic engine oil manufactured from advanced synthetic base fluids, high quality mineral oils and the latest additive technology. This grade is designed for use in the latest petrol and diesel engines fitted to passenger cars and light commercial vehicles. Multivis 10W/40 will protect camshafts, critical valve gear and bearings from wear, even under severe cold start conditions, as well as controlling rust and corrosion. Multivis 10W/40 has extremely good high temperature performance and will control deposits and keep components clean, helping to maintain operating integrity.

Applications

Multivis 10W/40 is recommended for use in 4-stroke petrol and diesel engines, including turbocharged and supercharged units, fitted in passenger cars and light commercial vehicles, where an oil of this type and specification is required.

Multivis 10W/40 can also be used in ATVs (with dry clutches), horticultural equipment and generator sets.

Performance Levels

API SL / SJ / CF
ACEA A3 / B4 - 08
MB 229.1
VW 501.01 / 505.00

Physical Characteristics

Density at 15 °C	0.88
Kinematic Viscosity at 100 °C, cSt.	14.5
Kinematic Viscosity at 40 °C, cSt.	90
Viscosity Index	150
Flash Point (Open) °C	200
TBN, mg/KOH/g	9
Sulphated Ash, %Wt.	1.3
Pour Point, °C	-35

(TDS Multivis 10W/40 – Issue 11 181110)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL

Telephone (01743) 232200

Fax (01743) 353584